



FUJIFILM LTO Ultrium 9 is the strategic choice for a transforming world. LTO 9 has a storage capacity of 18/45TB native/compressed, air gap security to protect against ransomware, and has the lowest energy consumption and CO2 emissions compared to other storage options. **Use less energy, store more data, and get more done with the next generation of our data tape.**^





### **Material Numbers**

FB LTO-9: 16659047

FB LTO-9 BC: 81110001744 FB LTO-9 LIB: 16671693

FB LTO-9 LIB BC: 81110001745 FB LTO-9 50PK BC: 81110001746

FB LTO-9 WORM: 16659059 FB LTO-9 WORM BC: 81110001747

# **Expand Your Capacity**

Fujifilm's Barium Ferrite technology has enabled LTO Ultrium 9 to achieve a native/compressed capacity of 18.0/45.0TB\* by recording 8,960 data tracks within 12.65mm tape width. With the utilization of multi-channel recording technology, LTO 9 features native/compressed transfer rates of up to 400/1000MB\* per second.

### **Specifications**

	Capacity (Native / Compressed)	18/	тв		
BASIC SPECIFICATIONS	Transfer Rate (Native / Compressed)	Up to 400/1000MB* per second			
	Number of Tracks	8,960			
PHYSICAL CHARACTERISTICS	Tape Width	12.65mm			
	Tape Thickness	5.2µm			
	Tape Length	1035m			
	Cartridge Dimensions	*1-21.5(l) x 105.4(w) x 102.0mm(h) (0.85" x 4.15" x 4.02") [L x W x			
		Allowable Operating Environment**	Recommended Operating Environment**		
ENVIRONMENTAL CONDITIONS	Temperature	15°C to 35°C	15°C to 25°C		
	Relative Humidity	20% to 80%	20% to 50%		
	Dew Point	22°C max	22°C max		

<sup>\*</sup>Assumes 2.5:1 data compression. Transfer rate is drive dependent.

# **LTO Ultrium Tape Drive Compatibility Chart**

Cartridge	Drive								
	Ultrium 3	Ultrium 4	Ultrium 5	Ultrium 6	Ultrium 7	Ultrium 8	Ultrium 9		
Ultrium 3	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible	Not Compatible	Not Compatible		
Ultrium 3 WORM	Read/Write Once	Read/Write Once	Read Only	Not Compatible	Not Compatible	Not Compatible	Not Compatible		
Ultrium 4	Not Compatible	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible	Not Compatible		
Ultrium 4 WORM	Not Compatible	Read/Write Once	Read/Write Once	Read Only	Not Compatible	Not Compatible	Not Compatible		
Ultrium 5	Not Compatible	Not Compatible	Read/Write	Read/Write	Read Only	Not Compatible	Not Compatible		
Ultrium 5 WORM	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Read Only	Not Compatible	Not Compatible		
Ultrium 6	Not Compatible	Not Compatible	Not Compatible	Read/Write	Read/Write	Not Compatible	Not Compatible		
Ultrium 6 WORM	Not Compatible	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Not Compatible	Not Compatible		
Ultrium 7	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write	Read/Write	Not Compatible		
Ultrium 7 WORM	Not Compatible	Not Compatible	Not Compatible	Not Compatible	Read/Write Once	Read/Write Once	Not Compatible		
Ultrium 8	Not Compatible	Read/Write	Read/Write						
Ultrium 8 WORM	Not Compatible	Read/Write Once	Read/Write Once						
Ultrium 9	Not Compatible	Read/Write							
Ultrium 9 WORM	Not Compatible	Read/Write Once							
Ultrium UCC*	Compatible								



Fujifilm's LTO Ultrium Universal Cleaning Cartridge is designed for use with all Ultrium 1-9 tape drives.

#### More Data Storage Solutions @ https://datastorage-na.fujifilm.com/lto-tape-data-storage

FUJIFILM, VALUE FROM INNOVATION and the BARIUM FERRITE logo are trademarks of FUJIFILM Corporation and its affiliates. LINEAR TAPE-OPEN, LTO, the LTO Logo, ULTRIUM and the ULTRIUM Logo are registered trademarks of Hewlett Packard Enterprise, International Business Machines Corporation and Quantum Corporation in the US and other countries. © 2021 FUJIFILM Recording Media U.S.A., Inc. All Rights Reserved.

<sup>\*\*</sup>Local tape temperature in excess of 52°C may cause permanent tape damage

<sup>\*</sup>UCC = Universal Cleaning Cartridge